



STOPGAP P121

Acrylic Primer

PRODUCT DATA

INTRODUCTION

STOPGAP P121 is an acrylic primer designed to promote the application characteristics of STOPGAP 1100 GYPSUM, and other suitable STOPGAP smoothing underlayments, to calcium sulphate screeds e.g. anhydrite. It prevents unacceptably rapid drying of adhesives and smoothing underlayments. It is non-flammable and suitable for use over normal underfloor heating installations. STOPGAP P121 is coloured blue to provide the user with visual control of coverage uniformity.

PREPARATION

Floor surfaces must be suitably prepared; sound, smooth, dry (<75%RH) and free from contaminants that may prevent adhesion. Calcium sulphate screeds e.g. anhydrite should be prepared in accordance with manufacturers instructions and thoroughly vacuumed to remove any remaining dust prior to the application of STOPGAP P121. The temperature of the surface must be above 5°C when the primer is applied to the subfloor and underfloor heating must be off for at least 48 hours before, during and after application. Ensure the subfloor is dry and incorporates an effective damp proof membrane.

MIXING AND APPLICATION

SHAKE WELL BEFORE USE

For dry (<75%RH) and suitably prepared calcium sulphate screeds, prime with two coats of STOPGAP P121. The first coat should be diluted 1 part primer to 1 part water. Once dry, prime with a second coat of neat P121.

Apply evenly to the whole surface to be treated and allow it to dry completely.

DRYING

This will vary depending on temperature, humidity and absorbency of subfloor. When applying onto suitably prepared calcium sulphate screed e.g. anhydrite, in good drying conditions, allow to fully dry to a tack free durable film. Drying time will be extended at lower temperatures.

PRECAUTIONS

Avoid excessive trafficking of the subfloor once the primer has dried.

TOOLS

Paint roller or medium stiff brush.

CLEANING

Wash tools with warm water immediately after use.

STORAGE

Store between 5°C and 30°C. Protect from frost.

SHELF LIFE

12 months in unopened containers and stored under good conditions.

TECHNICAL INFORMATION

Colour	Blue
Coverage Rates (Approx.)	10m ² per litre depending on the condition and absorbency of the subfloor

HOW MUCH MATERIAL?

PACK SIZE	COVERAGE
5 litre	50m ²

Note: Coverage rates will depend on the condition and absorbency of the subfloor.



FEATURES

- Suitable for calcium sulphate screeds
- Prevents the rapid drying of adhesives and smoothing underlayments.
- Pigmented to provide coverage control

PACKAGING

5 litre bottle

HEALTH AND SAFETY ADVICE

This product is not classified. Obtain the relevant Safety Data Sheet and follow the advice given. These can be found at www.f-ball.co.uk alternatively, these can be requested from the point of purchase or from F. Ball and Co. Ltd. at the address below.

Site conditions vary, to ensure this product is suitable and to confirm this data sheet is current please contact our Technical Service Department.

For further information about F. Ball products or more detailed technical assistance, please contact:

F. Ball and Co. Ltd.
Churnetside Business Park
Station Road, Cheddleton, Leek
Staffordshire ST13 7RS
United Kingdom

Tel: +44 (0) 1538 361633
Email: mail@f-ball.com

www.f-ball.com