

Primo Safe.T

Datasheet

Classification	Norm	Tarkett Value
Product type	EN 13845	Homogeneous vinyl floor covering
Commercial classification	ISO 10874	34 Very Heavy
Industrial classification	ISO 10874	43 Heavy
Characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	2 mm
Total weight	ISO 23997	3000 g/m ²
Surface treatment		Safety Clean XP
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance		0019-0048-DoP-2013-07
Reaction to fire	EN 13501-1	Bfl-s1
Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance (m ² K/W)	ISO 10456	$\sim 0,010$ m ² •K/W
Slip resistance	EN 13893	Class DS ($\mu \geq 0.30$)
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	≤ 0.10 mm Best measured value: 0,03 mm
Dimensional stability	EN ISO 23999	0.4%
Slip resistance	DIN 51130	R10
Slip resistance	DIN 51097	C
Seam Strength Average Value	EN 684	≥ 400 N/50mm
Castor chair effect	ISO 4918	Suitable
Colour fastness to light	ISO 105-B02	≥ 6
Underfloor heating	BS 8203	Suitable (subfloor temperature maximum 27°C)
Curl resistance to heat	EN ISO 23999	≤ 8 mm
Chemical resistance	ISO 26987	Good resistance
Bacteria Resistance	ISO 846 Part C	Does not promote growth
Wetroom approval	EN 13553 Annex A	Watertight
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value
Recyclability through ReStart®		Recyclable
Total recycled content		25.5 %
TVOC emissions after 28 days	EN 16516	Platinum (≤ 10 µg/m ³)
Dimensions and designs		
Roll		Roll 2x23m
Number of designs available		15



The above information is subject to modification for the benefit of further improvement (05/09/2023). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com> Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.